

TECHNICAL DATA**RR 390 ENDURO****CHASSIS**

Frame	Molybdenum steel with double cradle split above the exhaust port
Wheelbase	1480 mm
Max length	2180 mm
Max width	830 mm
Max height	1270 mm
Seat height	930 mm
Ground clearance	315 mm
Footrest height	407 mm
Dry weight	107,5 kg (front 52,7 kg; rear 54,8 kg)
Fuel tank capacity	9,0 l.
Reserve	2,3l.
Cooling system capacity	1,4 l.
Front suspension	Hydraulic USD fork with ø48 mm shaft
Rear suspension	Monoshock with progressive compound lever
Shock absorber stroke	132 mm
Front wheel travel	295 mm
Rear wheel travel	290 mm
Front brake	Wave disc ø260 mm and double-piston floating caliper
Rear brake	Wave disc ø240 mm and single-piston floating caliper
Front rim	21 x 1,6 - 36 holes
Rear rim	18 x 2,15 - 36 holes
Front tyre	90/90 - 21
Rear tyre	140/80 -18

ENGINE

Type	Single cylinder, 4-stroke, liquid-cooled
Bore	88 mm
Stroke	63,4 mm
Displacement	385,6 cc
Compression ratio	12,48:1
Valve train	DOHC finger follower / 4 titanium valve
Starter	Electric starter
ACG	Kokusan
Spark plug	NGK LKAR 8A-9
Lubrication	2 oil pumps
Fuel system	Elldor dual electronic injection
Throttle body	ø 42 mm - Synerject
Clutch	wet multi-disc clutch
Primary drive	Z.28/76
Transmission	6 gears
Final transmission	chain
Engine oil	SAE 10W/50 0,8 l. + SAE 10W/40 0,8 l.
Consumption l/100 km	3,3
Pollution Co2 [g/km]	79